




GENERAL

Credential Support
Ingress Protection

Bluetooth (BLE), RFID Card, and PIN
IP65

COSEC VEGA CAE:- EM Proximity Card

COSEC VEGA CAM:- MIFARE Classic®, DESFire EV1 and EV2(Read/Write), NFC Tag

Card

COSEC VEGA CAI:- HID iClass Card Support (Read/Write), HID Prox, EM Prox, Desfire EV1 & EV2 (CSN Read) and Mifare Classic (CSN Read), NFC Tag

*MIFARE and MIFARE Classic® are trademarks of NXP B.V.

CAPACITY

Max. Users 50,000
Event Buffer 500,000
Cards per User Up to 2

COMMUNICATION

Wi-Fi Yes (802.11 b/g/n)
WLAN (802.11 b/g/n) Frequency: 2.4 GHz, Frequency Range: 2412 MHz to 2485 MHz
Bluetooth (BLE 4.0) Frequency: 2.4 GHz, Frequency Range: 2402 MHz to 2480 MHz
Ethernet Yes (10/100 Mbps)
PoE Yes (IEEE 802.11 b/g/n)
RS-232 Yes
Mobile Broadband Yes (3G/4G/LTE)
Wiegand Yes (Selectable IN/OUT)
IN: 26 Bit format
OUT: Configurable
USB 1 USB Port (Data Transfer and 3G/4G/LTE Dongle)

INTERFACE

Exit Switch Yes

Door Status Sense	Programmable NO, NC, Supervised
Door Lock Relay	30V DC @ 1A, Form C, DPDT Relay
Door Lock Power	12V DC @ 0.5A (Power to external Lock from Device)
Aux-In	30V DC @2 A (Power to lock from an External power source)
Aux-Out	Yes
Reader Interface Types	Yes
	RS-232, and Wiegand

HARDWARE

CPU	800 MHz ARM Cortex A8 Based Processor
Memory	256 MB Flash + 512 MB DDR3 RAM
Micro SD Card	Yes (Inbuilt 16 GB)
Display	3.5" TFT Display with Capacitive Touch Panel
Display Size	320 x 240 Pixel
Buzzer	Yes
Operating Temperature	0°C to +50°C (32°F to 122°F)
Humidity	5% to 95% RH Non-Condensing
Tamper Detection	Yes
Power	12V DC @ 2A
Power to Door Lock	12V DC @ 0.5A (Power to Lock from Device)
	30V DC @1 A (Power to lock from External Adaptor)
Dimensions (W x H x D)	91mm x 186mm x 38mm (3.58" x 7.32" x 1.49")
Weight	0.54 Kgs (1.19 lbs.)

CERTIFICATES

CE, FCC, BIS, ROHS, IP65, Shock and Vibration Proof

COMPATIBILITY

System Integration	API for Software Integration
Operational Modes	Direct Door with COSEC CENTRA/VYOM Panel Door with COSEC PANEL200P

INSTALLATION

Wall Mount	Yes
------------	-----

ACCESSORIES

Power Adapter	12VDC @ 2A (CE, FCC, UL, BIS)
Battery Backup	Yes

APPLICATIONS

Access Control
Time-Attendance
Visitor Management
Contract Workers' Management
Cafeteria Management

Job Processing and Costing

**Due to continuous technology upgradations, product specifications are subject to change without notice.*

ABOUT MATRIX

Established in 1991, Matrix is a leader in Security and Telecom solutions for modern organizations. Matrix offers a comprehensive range of solutions for IP Video Surveillance, Access Control, Time-Attendance, and Telecom applications. The solutions are designed to meet the communication and security requirements of large enterprises having offices in multiple locations, SMEs, and SMBs.

As an innovative, technology-driven, and customer-focused organization, Matrix is committed to keeping pace with the revolutions in the Security and Telecom industries. With around 40% of its human resources dedicated to the development of new products, Matrix has launched over 60 cutting-edge products and solutions.

IP Video Surveillance includes solutions like Video Management Systems, Network Video Recorders, and IP Cameras. Likewise, solutions in Access Control and Time-Attendance include Visitor Management Solutions, Elevator Access Control, Panels, Door Controllers, and Readers.

We offer Telecom Solutions such as Unified Communications, IP-PBX, Universal Media Gateways, VoIP and GSM Gateways, and Communication Endpoints. All these solutions are feature-rich, reliable, and conform to international standards.



MATRIX COMSEC

Head Office

394-GIDC, Makarpura, Vadodara-390 010,
India.

Ph: (+91) 265-613-7222

E-mail: Inquiry@MatrixComSec.com

Factory

19-GIDC, Waghodia,
Dist. Vadodara-391 760,
India.

Ph: (+91) 265-613-7222

MATRIX COMSEC - North America

2 Wickstead Crt, Brampton,
Ontario, L6R 1N8.

+1 408-643-0581 (USA)

+1 437-266-1005 (Canada)

www.MatrixComSec.com